



CAC



COOK



Features, Performance and Dimension Data

CAC-P (Pedestal Mounted)	2
CAC-W (Wall Mounted)	3
CAC-FH (Floor Mounted High Velocity/High Volume)	4
CAC-MH (Mobile High Velocity/High Volume)	5
CAC-CH (Ceiling Mounted High Velocity/High Volume)	6
CAC-WH (Wall Mounted High Velocity/High Volume)	7
CAC-WW (Wall Mounted Washdown)	8
CAC-WX (Wall Mounted Hazardous Duty)	9
CAC-WO (Wall Mounted Oscillating)	10
CAC-PO (Pedestal Mounted Oscillating)	11
CAC-M (Mobile)	12
CAC-DF (Dock Fan)	12




Loren Cook Company certifies that the CAC-P shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.



Type CAC-P is furnished standard with UL 507 listing.



Type CAC-P is furnished standard with CSA Certification (Standard 113-M1984).



Standard Construction Features

- High efficiency stamped aluminum prop
- Locking tilt and adjustable height powder coated pedestal
- OSHA compliant powder coated steel wire guard
- 115 V, 60 Hz, two-speed, open drip proof thermal protected motor
- Factory pre-wired 10 foot cord

Performance Data


Catalog Number	Prop Diameter	Motor Speeds	CFM (High / Low)	HP	RPM (High/Low)	Watts	Operating Amps (High/Low)	CFM/Watts (High/Low)	No. of Blades
18CAC11P	18"	2	2660 / 1925	1/10	1100/ 800	160	2.1/1.1	16.63/17.99	3
20CAC11P	20"		3717 / 2631	1/8		194	2.1/1.5	19.16/17.42	
24CAC11P	24"		5465 / 3805	1/4		251	2.4/2.1	21.77/19.61	
30CAC11P	30"		7261 / 4674			277	2.7/2.1	26.21/24.22	

AMCA Certified Rating Seal applies to airflow rate at free delivery only. Speed (RPM or RPS) shown is nominal. Performance based on actual speed of test. Performance ratings do not include the effects of appurtenances in the airstream.


Velocity Profiles

Catalog Number	Air Velocity - High Speed / Low Speed (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
18CAC11P	360 / 310	110 / 95	-	-
20CAC11P	400 / 360	195 / 205	150 / 130	-
24CAC11P	590 / 300	360 / 180	250 / 115	175 / -
30CAC11P	715 / 680	370 / 350	280 / 250	170 / 140


18CAC11P




20CAC11P



24CAC11P



30CAC11P



Dimension Data

Catalog Number	A	B	C	D		E	Ship Weight
				Min.	Max.		
18CAC11P	20-1/2	6-1/8	12	56-5/8	83-7/8	26	65
20CAC11P	22-1/2	12-1/4	6-1/8	56-5/8	83-7/8	26	70
24CAC11P	26-1/2	12-1/4	6-1/8	56-5/8	83-7/8	26	73
30CAC11P	33	14-1/4	8-1/8	56-5/8	83-7/8	26	85

All dimensions in inches. Weights in lbs.

Standard Construction Features

- High efficiency stamped aluminum prop
- Multi-directional wall or ceiling powder coated mounting bracket
- OSHA compliant powder coated steel wire guard
- 115 V, 60 Hz, two-speed, open drip proof thermal protected motor
- Factory pre-wired 10 foot cord

Performance Data


Catalog Number	Prop Diameter	Motor Speeds	CFM (High / Low)	HP	RPM (High/Low)	Watts	Operating Amps (High/Low)	CFM/Watts (High/Low)	No. of Blades	
18CAC11W	18"	2	2660 / 1925	1/10	1100/ 800	160	2.1/1.1	16.63/17.99	3	
20CAC11W	20"		3717 / 2631	1/8		194	2.1/1.5	19.16/17.42		
24CAC11W	24"		5465 / 3805	1/4		251	2.4/2.1	21.77/19.61		
30CAC11W	30"		7261 / 4674			277	2.7/2.1	26.21/24.22		

AMCA Certified Rating Seal applies to airflow rate at free delivery only. Speed (RPM or RPS) shown is nominal. Performance based on actual speed of test. Performance ratings do not include the effects of appurtenances in the airstream.


Velocity Profiles

Catalog Number	Air Velocity - High Speed / Low Speed (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
18CAC11W	360 / 310	110 / 95	-	-
20CAC11W	400 / 360	195 / 205	150 / 130	-
24CAC11W	590 / 300	360 / 180	250 / 115	175 / -
30CAC11W	715 / 680	370 / 350	280 / 250	170 / 140


18CAC11W




20CAC11W



24CAC11W




30CAC11W



Dimension Data

Catalog Number	A	B	C	D	E	Ship Weight
18CAC11W	20-1/2	17-3/8	22-1/2	12	6-1/8	26
20CAC11W	22-1/2	17-3/4	23-1/4	12-1/4	6-1/8	42
24CAC11W	26-1/2	17-3/4	23-1/4	12-1/4	6-1/8	43
30CAC11W	33	17-3/4	25-1/4	14-1/4	8-1/2	51

All dimensions in inches. Weights in lbs.




Loren Cook Company certifies that the CAC-W shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.




Type CAC-W is furnished standard with UL 507 listing.



Type CAC-W is furnished standard with CSA Certification (Standard 113-M1984).



CAC-FH Floor Mounted High Velocity/High Volume



Standard Construction Features

- High efficiency, high volume, high velocity one piece cast aluminum prop
- Heavy duty powder coated locking adjustable tilt, non-tipping stand
- OSHA compliant steel wire guard
- Totally enclosed ball bearing motor
- Factory pre-wired pigtail cord


Performance Data

Catalog Number	Prop Dia.	CFM	HP	RPM	Volts (High/Low)	Phase	Operating Amps
18CAC17FH1	18"	2773	1/4	1750	115/230	1	4.2/2.1
18CAC17FH3	18"	2792	1/4	1750	208-220/440	3	1.0/0.6
24CAC11FH1	24"	4684	1/3	1140	115/230	1	6.4/3.2
24CAC17FH1	24"	6995	1	1725	115/230	1	13.0/6.5
24CAC17FH3	24"	6949	1	1725	208-220/440	3	3.3/1.6
30CAC17FH1	30"	10362	2	1725	115/230	1	14.5/7.2
30CAC17FH3	30"	10029	2	1725	208-220/440	3	5.0/2.4
36CAC11FH1	36"	11391	1	1140	115/230	1	10.7/5.5
36CAC11FH3A	36"	11418	1	1140	208-220/440	3	3.9/1.9
36CAC11FH3B	36"	15053	2	1150	208-220/440	3	6.4/3.2


Velocity Profiles

Catalog Number	Air Velocity - (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
18CAC17FH1	440	240	100	-
18CAC17FH3	440	240	100	-
24CAC11FH1	530	350	240	140
24CAC17FH1	790	520	360	220
24CAC17FH3	790	520	360	220
30CAC17FH1	1160	760	520	320
30CAC17FH3	1160	760	520	320
36CAC11FH1	1280	840	580	350
36CAC11FH3A	1280	840	580	350
36CAC11FH3B	1690	1110	760	460


18CAC17FH1 & 18CAC17FH3




24CAC11FH1




24CAC17FH1 & 24CAC17FH3




30CAC17FH1 & 30CAC17FH3



36CAC11FH1 & 36CAC11FH3A



36CAC11FH3B



Dimension Data

Catalog Number	A	B	C	Ship Weight
18CAC17FH1	26-1/4	36-7/8	31-3/4	156
18CAC17FH3	26-1/4	36-7/8	31-3/4	156
24CAC11FH1	32-3/16	36-7/8	34-3/4	204
24CAC17FH1	32-3/16	36-7/8	34-3/4	204
24CAC17FH3	32-3/16	36-7/8	34-3/4	204
30CAC17FH1	37-7/16	36-7/8	37-13/16	290
30CAC17FH3	37-7/16	36-7/8	37-13/16	290
36CAC11FH1	44-7/16	36-7/8	40-7/8	328
36CAC11FH3A	44-7/16	36-7/8	40-7/8	328
36CAC11FH3B	44-7/16	36-7/8	40-7/8	328

All dimensions in inches. Weights in lbs.

Standard Construction Features

- High efficiency, high volume, high velocity one piece cast aluminum prop
- Heavy duty powder coated locking adjustable tilt, non-tipping stand
- OSHA compliant steel wire guard
- Totally enclosed ball bearing motor
- Factory pre-wired pigtail cord
- Tubular steel positioning handle
- Large diameter wheels


Performance Data

Catalog Number	Prop Dia.	CFM	HP	RPM	Volts (High/Low)	Phase	Operating Amps
18CAC17MH1	18"	2773	1/4	1750	115/230	1	4.2/2.1
18CAC17MH3	18"	2792	1/4	1750	208-220/440	3	1.0/0.6
24CAC11MH1	24"	4684	1/3	1140	115/230	1	6.4/3.2
24CAC17MH1	24"	6995	1	1725	115/230	1	13.0/6.5
24CAC17MH3	24"	6949	1	1725	208-220/440	3	3.3/1.6
30CAC17MH1	30"	10362	2	1725	115/230	1	14.5/7.2
30CAC17MH3	30"	10029	2	1725	208-220/440	3	5.0/2.4
36CAC11MH1	36"	11391	1	1140	115/230	1	10.7/5.5
36CAC11MH3A	36"	11418	1	1140	208-220/440	3	3.9/1.9
36CAC11MH3B	36"	15053	2	1150	208-220/440	3	6.4/3.2


Velocity Profiles

Catalog Number	Air Velocity - (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
18CAC17MH1	440	240	100	-
18CAC17MH3	440	240	100	-
24CAC11MH1	530	350	240	140
24CAC17MH1	790	520	360	220
24CAC17MH3	790	520	360	220
30CAC17MH1	1160	760	520	320
30CAC17MH3	1160	760	520	320
36CAC11MH1	1280	840	580	350
36CAC11MH3A	1280	840	580	350
36CAC11MH3B	1690	1110	760	460


18CAC17MH1 & 18CAC17MH3




24CAC11MH1




24CAC17MH1 & 24CAC17MH3




30CAC17MH1 & 30CAC17MH3



36CAC11MH1 & 30CAC11MH3A




36CAC11MH3B




Dimension Data

Catalog Number	A	B	C	D	E	Ship Weight
18CAC17MH1	32-7/8	34	14-13/16	46-9/16	30-7/8	227
18CAC17MH3	32-7/8	34	14-13/16	46-9/16	30-7/8	227
24CAC11MH1	35-7/8	34	14-13/16	49-9/16	31-7/8	275
24CAC17MH1	35-7/8	34	14-13/16	49-9/16	31-7/8	275
24CAC17MH3	35-7/8	34	14-13/16	49-9/16	31-7/8	275
30CAC17MH1	42-1/16	34	14-13/16	52-5/8	31-7/8	361
30CAC17MH3	42-1/16	34	14-13/16	52-5/8	31-7/8	361
36CAC11MH1	48-1/8	34	14-13/16	55-11/16	32-7/8	399
36CAC11MH3A	48-1/8	34	14-13/16	55-11/16	32-7/8	399
36CAC11MH3B	48-1/8	34	14-13/16	55-11/16	32-7/8	399

All dimensions in inches. Weights in lbs.



CAC-CH Ceiling Mounted High Velocity/High Volume



Standard Construction Features

- High efficiency, high volume, high velocity one piece cast aluminum prop
- Heavy duty powder coated locking adjustable tilt, non-tipping stand
- OSHA compliant steel wire guard
- Totally enclosed ball bearing motor
- Factory pre-wired pigtail cord


Performance Data

Catalog Number	Prop Dia.	CFM	HP	RPM	Volts (High/Low)	Phase	Operating Amps
18CAC17CH1	18"	2773	1/4	1750	115/230	1	4.2/2.1
18CAC17CH3	18"	2792	1/4	1750	208-220/440	3	1.0/0.6
24CAC11CH1	24"	4684	1/3	1140	115/230	1	6.4/3.2
24CAC17CH1	24"	6995	1	1725	115/230	1	13.0/6.5
24CAC17CH3	24"	6949	1	1725	208-220/440	3	3.3/1.6
30CAC17CH1	30"	10362	2	1725	115/230	1	14.5/7.2
30CAC17CH3	30"	10029	2	1725	208-220/440	3	5.0/2.4
36CAC11CH1	36"	11391	1	1140	115/230	1	10.7/5.5
36CAC11CH3A	36"	11418	1	1140	208-220/440	3	3.9/1.9
36CAC11CH3B	36"	15053	2	1150	208-220/440	3	6.4/3.2


Velocity Profiles

Catalog Number	Air Velocity - (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
18CAC17MH1	440	240	100	-
18CAC17MH3	440	240	100	-
24CAC11MH1	530	350	240	140
24CAC17MH1	790	520	360	220
24CAC17MH3	790	520	360	220
30CAC17MH1	1160	760	520	320
30CAC17MH3	1160	760	520	320
36CAC11MH1	1280	840	580	350
36CAC11MH3A	1280	840	580	350
36CAC11MH3B	1690	1110	760	460


18CAC17CH1 & 18CAC17CH3




24CAC11CH1




24CAC17CH1 & 24CAC17CH3




30CAC17CH1 & 30CAC17CH3



36CAC11CH1 & 36CAC11CH3A



36CAC11CH3B



Dimension Data

Catalog Number	A	B	C	D	E	F	G	H	Ship Weight
18CAC17CH1	4-11/16	12	21-1/2	21-3/8	22-7/8	26-1/4	27-1/16	36-1/4	168
18CAC17CH3	4-11/16	12	21-1/2	21-3/8	22-7/8	26-1/4	27-1/16	36-1/4	168
24CAC11CH1	5-11/16	12	27-3/8	23-3/8	22-7/8	32-1/4	27-1/16	39-1/4	218
24CAC17CH1	5-11/16	12	27-3/8	23-3/8	22-7/8	32-1/4	27-1/16	39-1/4	218
24CAC17CH3	5-11/16	12	27-3/8	23-3/8	22-7/8	32-1/4	27-1/16	39-1/4	218
30CAC17CH1	5-11/16	12	33-5/8	23-3/8	28-7/16	38-1/2	32-5/8	47-7/8	302
30CAC17CH3	5-11/16	12	33-5/8	23-3/8	28-7/16	38-1/2	32-5/8	47-7/8	302
36CAC11CH1	6-11/16	12	39-5/8	25-3/8	28-7/16	44-1/2	32-5/8	50-7/8	340
36CAC11CH3A	6-11/16	12	39-5/8	25-3/8	28-7/16	44-1/2	32-5/8	50-7/8	340
36CAC11CH3B	6-11/16	12	39-5/8	25-3/8	28-7/16	44-1/2	32-5/8	50-7/8	340

All dimensions in inches. Weights in lbs.

Standard Construction Features


- High efficiency, high volume, high velocity one piece cast aluminum prop
- Heavy duty powder coated locking adjustable tilt and rotation ceiling bracket
- OSHA compliant steel wire guard
- Totally enclosed ball bearing motor
- Factory pre-wired pigtail cord

Performance Data


Catalog Number	Prop Dia.	CFM	HP	RPM	Volts (High/Low)	Phase	Operating Amps
18CAC17WH1	18"	2773	1/4	1750	115/230	1	4.2/2.1
18CAC17WH3	18"	2792	1/4	1750	208-220/440	3	1.0/0.6
24CAC11WH1	24"	4684	1/3	1140	115/230	1	6.4/3.2
24CAC17WH1	24"	6995	1	1725	115/230	1	13.0/6.5
24CAC17WH3	24"	6949	1	1725	208-220/440	3	3.3/1.6
30CAC17WH1	30"	10362	2	1725	115/230	1	14.5/7.2
30CAC17WH3	30"	10029	2	1725	208-220/440	3	5.0/2.4
36CAC11WH1	36"	11391	1	1140	115/230	1	10.7/5.5
36CAC11WH3A	36"	11418	1	1140	208-220/440	3	3.9/1.9
36CAC11WH3B	36"	15053	2	1150	208-220/440	3	6.4/3.2

Velocity Profiles


Catalog Number	Air Velocity - (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
18CAC17WH1	440	240	100	-
18CAC17WH3	440	240	100	-
24CAC11WH1	530	350	240	140
24CAC17WH1	790	520	360	220
24CAC17WH3	790	520	360	220
30CAC17WH1	1160	760	520	320
30CAC17WH3	1160	760	520	320
36CAC11WH1	1280	840	580	350
36CAC11WH3A	1280	840	580	350
36CAC11WH3B	1690	1110	760	460




18CAC17WH1 & 18CAC17WH3




24CAC11WH1




24CAC17WH1 & 24CAC17WH3




30CAC17WH1 & 30CAC17WH3



36CAC11WH1 & 36CAC17WH3A



36CAC11WH3B



Dimension Data

Catalog Number	A	B	C	D	E	F	G	H	J	K	L	M	Ship Weight
18CAC17WH1	3-11/16	14	11-1/2	21-1/2	21-3/8	22-7/8	31-1/2	39-1/4	48-7/8	26-1/4	38-5/8	25-1/2	248
18CAC17WH3	3-11/16	14	11-1/2	21-1/2	21-3/8	22-7/8	31-1/2	39-1/4	48-7/8	26-1/4	38-5/8	25-1/2	248
24CAC11WH1	4-11/16	14	11-1/2	27-3/8	23-3/8	22-7/8	31-1/2	39-1/4	51-1/2	32-1/4	41-5/8	25-1/2	298
24CAC17WH1	4-11/16	14	11-1/2	27-3/8	23-3/8	22-7/8	31-1/2	39-1/4	51-1/2	32-1/4	41-5/8	25-1/2	298
24CAC17WH3	4-11/16	14	11-1/2	27-3/8	23-3/8	22-7/8	31-1/2	39-1/4	51-1/2	32-1/4	41-5/8	25-1/2	298
30CAC17WH1	4-11/16	14	11-1/2	33-5/8	23-3/8	28-7/16	31-1/2	44-7/8	60-1/4	38-1/2	44-3/4	25-1/2	382
30CAC17WH3	4-11/16	14	11-1/2	33-5/8	23-3/8	28-7/16	31-1/2	44-7/8	60-1/4	38-1/2	44-3/4	25-1/2	382
36CAC11WH1	5-11/16	14	11-1/2	39-5/8	25-3/8	28-7/16	31-1/2	44-7/8	63-1/4	44-1/2	47-3/4	25-1/2	420
36CAC11WH3A	5-11/16	14	11-1/2	39-5/8	25-3/8	28-7/16	31-1/2	44-7/8	63-1/4	44-1/2	47-3/4	25-1/2	420
36CAC11WH3B	5-11/16	14	11-1/2	39-5/8	25-3/8	28-7/16	31-1/2	44-7/8	63-1/4	44-1/2	47-3/4	25-1/2	420

All dimensions in inches. Weights in lbs.





Loren Cook Company certifies that the CAC-WW shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.



Type CAC-WW is furnished standard with UL 507 listing.



Type CAC-WW is furnished standard with CSA Certification (Standard 113-M1984).



Standard Construction Features

- High efficiency stamped aluminum prop
- Multi-directional wall or ceiling powder coated mounting bracket
- OSHA compliant Zinc-plated steel wire guard
- BISSC and NEMA standard waterproof totally enclosed thermal protected motor
- Motor coating USDA approved white epoxy

Performance Data


Catalog Number	Prop Diameter	CFM	HP	RPM	Watts	Operating Amps	CFM/Watt
20CAC17WW	20"	4036	1/4	1700	208	2.6	19.4
24CAC17WW	24"	6849	1/3	1700	389	4.0	17.6
30CAC11WW	30"	10001	1/2	1140	495	4.7	20.2

AMCA Certified Rating Seal applies to airflow rate at free delivery only. Speed (RPM or RPS) shown is nominal. Performance based on actual speed of test. Performance ratings do not include the effects of appurtenances in the airstream.


Velocity Profiles

Catalog Number	Air Velocity - (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
20CAC17WW	580	240	155	75
24CAC17WW	735	245	170	135
30CAC11WW	750	310	180	-


20CAC17WW



24CAC17WW



30CAC11WW



Dimension Data

Catalog Number	A	B	C	D	E	Ship Weight
20CAC17WW	22-1/2	17-3/4	23	13-11/16	6-1/8	38
24CAC17WW	26-1/2	17-3/4	23	13-11/16	6-1/8	38
30CAC11WW	33	18-1/16	25-9/16	17-3/16	8-1/2	57

All dimensions in inches. Weights in lbs.

Standard Construction Features

- High efficiency spark-resistant cast aluminum prop
- Heavy duty wall mounting bracket
- OSHA compliant Zinc-plated steel wire guard
- UL Listed and CSA Certified Class I, Div. 1, Group D; Class II, Div. 1, Groups E, F & G totally enclosed thermal protected motor



Performance Data

Catalog Number	Prop Diameter	CFM	HP	RPM	Watts	Operating Amps	CFM/Watt
24CAC11WX	24"	5486	1/4	1140	343	6.0	15.99
30CAC11WX	30"	10937	3/4	1140	701	7.0	15.60

AMCA Certified Rating Seal applies to airflow rate at free delivery only. Speed (RPM or RPS) shown is nominal. Performance based on actual speed of test.


Velocity Profiles

Catalog Number	Air Velocity - (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
24CAC11WX	520	280	200	125
30CAC11WX	335	385	295	260




Loren Cook Company certifies that the CAC-WX shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.

24CAC11WX




30CAC11WX




Dimension Data

Catalog Number	A	B	C	D	E	F	Ship Weight
24CAC11WX	7	26-1/2	20	23-3/8	19	6-1/8	56
30CAC11WX	7	33	20	25-7/16	21-7/8	8-3/16	98

All dimensions in inches. Weights in lbs.



CAC-WO Wall Mounted Oscillating




Loren Cook Company certifies that the CAC-WO shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.



Type CAC-WO is furnished standard with UL 507 listing.



Type CAC-WO is furnished standard with CSA Certification (Standard 113-M1984).



Standard Construction Features

- High efficiency stamped aluminum prop
- Powder coated mounting bracket
- OSHA compliant powder coated steel wire guard
- 90 degree wide area oscillation
- 115 V, 60 Hz, two-speed, open drip proof thermal protected motor
- Factory pre-wired 10 foot cord

Performance Data


Catalog Number	Prop Diameter	Motor Speeds	CFM	HP	RPM (High/Low)	Watts	Operating Amps (High/Low)	CFM/Watt (High/Low)	No. of Blades
20CAC11WO	20"	2	3403/3078	1/4	1075/800	224	3.4/1.3	15.19/24.62	2
24CAC11WO	24"		5537/4468			300	3.4/1.7	18.46/21.58	3
30CAC11WO	30"		9573/8878			474	4.5/3.4	20.20/23.06	2

AMCA Certified Rating Seal applies to airflow rate at free delivery only. Speed (RPM or RPS) shown is nominal. Performance based on actual speed of test.


Velocity Profiles

Catalog Number	Air Velocity - High Speed / Low Speed (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
20CAC11WO	400/350	190/180	90/85	-
24CAC11WO	410/325	185/145	80/60	-
30CAC11WO	710/650	340/310	175/160	-


20CAC11WO



24CAC11WO



30CAC11WO



Dimension Data

Catalog Number	A	B	C	D	E	Ship Weight
20CAC11WO	22-1/2	18-13/16	24-1/2	15-9/16	6-1/8	42
24CAC11WO	26-1/2	18-13/16	24-1/2	16-5/8	6-1/8	46
30CAC11WO	33	18-13/16	24-1/2	19	8-1/2	66

All dimensions in inches. Weights in lbs.

Standard Construction Features

- High efficiency stamped aluminum prop
- Adjustable height powder coated pedestal
- OSHA compliant powder coated steel wire guard
- 90 degree wide area oscillation
- 115 V, 60 Hz, two-speed, open drip proof thermal protected motor
- Factory pre-wired 10 foot cord

Performance Data


Catalog Number	Prop Diameter	Motor Speeds	CFM	HP	RPM (High/Low)	Watts	Operating Amps (High/Low)	CFM/Watt (High/Low)	No. of Blades
20CAC11PO	20"	2	3403/3078	1/4	1075/800	224	3.4/1.3	15.19/24.62	2
24CAC11PO	24"		5537/4468			300	3.4/1.7	18.46/21.58	3
30CAC11PO	30"		9573/8878	1/2		474	4.5/3.4	20.20/23.06	2

AMCA Certified Rating Seal applies to airflow rate at free delivery only. Speed (RPM or RPS) shown is nominal. Performance based on actual speed of test.


Velocity Profiles

Catalog Number	Air Velocity - High Speed / Low Speed (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
20CAC11PO	400/350	190/180	90/85	-
24CAC11PO	410/325	185/145	80/60	-
30CAC11PO	710/650	340/310	175/160	-


20CAC11PO



24CAC11PO



30CAC11PO



Dimension Data

Catalog Number	A	B	C	D		E	Ship Weight
				Min.	Max.		
20CAC11PO	22-1/2	15-9/16	6-1/8	57-11/16	84-15/16	33	74
24CAC11PO	26-1/2	16-5/8	6-1/8	57-11/16	84-15/16	33	78
30CAC11PO	33	19	8-1/8	57-11/16	84-15/16	33	98

All dimensions in inches. Weights in lbs.





Loren Cook Company certifies that the CAC-PO shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.



Type CAC-PO is furnished standard with UL 507 listing.



Type CAC-PO is furnished standard with CSA Certification (Standard 113-M1984).






Type CAC-M is furnished standard with UL 507 listing.



Type CAC-M is furnished standard with CSA Certification (Standard 113-M1984).



Standard Construction Features

- High efficiency stamped steel prop
- Powder coated housing with tubular steel handle
- OSHA compliant Zinc-plated steel wire guard
- Large diameter rubber tread wheels
- 115 V, 60 Hz, two-speed, open drip proof thermal protected motor
- Factory pre-wired switch and 10 foot cord


Performance Data

Catalog Number	Prop Diameter	CFM	RPM	HP	Operating Amps
36CAC08M	36"	9280	825	1/2	6.4

Velocity Profiles

Catalog Number	Air Velocity - (FPM)			
	Distance from Fan (Ft.)			
	20'	40'	60'	80'
36CAC08M	780	405	295	220

36CAC08M



Dimension Data

Catalog Number	A	B	C	D	E	Ship Weight
36CAC08M	39-1/2	32-1/2	40-1/2	14-11/16	18-1/16	110

All dimensions in inches. Weights in lbs.

Dock Fan CAC-DF

Standard Construction Features

- High efficiency stamped aluminum prop
- Heavy duty powder coated mounting bracket and extension arm
- OSHA compliant Zinc-plated steel wire guard
- 115 V, 60 Hz, two-speed, open drip proof thermal protected motor
- Factory pre-wired cord
- Pivoting spotlight


Performance Data

Catalog Number	Prop Diameter	CFM (High/Low)	HP	RPM	Operating Amps
20CAC16DF	20"	3150/2330	1/4	1625/1150	2.9

Velocity Profiles

Catalog Number	Air Velocity - (FPM)					
	Distance from Fan (Ft.)					
	8'	16'	24'	32'	40'	45'
20CAC16DF	290	150	130	100	60	50

20CAC16DF



Dimension Data

Catalog Number	A	B	C	D	E	F	G	H	J	K	Ship Weight
20CAC16DF	39-3/4	60-3/4	33-3/4	12-3/16	6	10	23-7/16	20-13/16	12-3/8	9-1/4	62


All dimensions in inches. Weights in lbs.



Type CAC-DF is furnished standard with UL 507 listing.



Type CAC-DF is furnished standard with CSA Certification (Standard 113-M1984).





LOREN COOK COMPANY

2015 E. DALE STREET
SPRINGFIELD, MO 65803-4637

417.869.6474

FAX 417.862.3820

lorencook.com