

# UL762

## UL 762 Listed for Restaurant Exhaust Appliances

Cook products, with UL 762 listing are designed to eject contaminated or grease-laden air. The products are UL listed to operate continuously at elevated temperatures, and continue operation during grease flare-up.

### Products UL Listed to Operate up to 300°F

VCR / VCR-HP / VCR-XP

VCRD / VCRD-HP / VCRD-XP

Lo-Pro (requires diverters)

CPV / CPA / CPA-A

QMX / QMX-HP / QMXU / QMXU-HP / QMXLE / QMXLE-HP

CIC

CPV, CPA, CPA-A, QMX, QMX-HP and CIC must be ordered with drain and access door to comply with UL requirements. Weather covers are required for outdoor applications. When airstream temperatures are expected to exceed 180°F, high temperature accessories may be required.

### Loren Cook Products UL Listed to Operate up to 500°F

CPS / CPS-A

CA / CA-SWSI Arrangement 1, 9 and 10

CA-4 / CA-4 SWSI Arrangement 1 and 2

CF / CF Arrangement 1, 9 and 10

CF-4 / CF-4 Arrangement 1 and 2

QMX / QMX-HP Arrangement 9

CIC

These Cook products must be ordered with drain and access door to comply with UL requirements. Weather covers are required for outdoor applications.

When airstream temperatures are expected to exceed 180°F, high temperature accessories may be required.

All of the units are intended for installation in accordance with the Standard of the National Fire Protection Association for the installation of Equipment for the Removal of Smoke and Grease-Laden Vapors from Commercial Cooking Equipment, NFPA 96.



UL listed for Restaurant Exhaust Appliances



**LOREN COOK COMPANY**

2015 E. DALE STREET  
SPRINGFIELD, MO 65803-4637  
417.869.6474  
FAX 417.862.3820  
lorencook.com



VCR / VCR-HP / VCR-XP  
VCRD / VCRD-HP / VCRD-XP



Lo-Pro - Shown with diverters



CPS / CPA / CPS-A / CPA-A  
Shown with weather cover



CA / CF



CA-4 / CF-4



QMX / QMX-HP



CIC



QMXLE / QMXLE-HP



QMXU / QMXU-HP