Zurn Aquaflush

Dependable · Long Lasting · Quality

Aquaflush Chemical and Clog Resistant Extended Life Diaphragm

- **Clog Resistant Linear Filtered By-Pass**
- **TPE Chemical Resistant Diaphragm and Seals Resist the Affect of Chloramine on Black Rubber by a Factor of 10**
- **ADA Compliant, No-Leak Handle Assembly**
- **High Pressure Vacuum Breaker**
- **Dezincafication Resistant Low Lead Brass**
- **Sensor Adaptable**
- **Three-Year Warranty**

Aquaflush has standard features that the competition offers only in their high-priced line of valves.

ZURN INDUSTRIES, INC.
COMMERCIAL BRASS OPERATION
5900 ELWIN BUCHANAN DRIVE
SANFORD, NC 27330
PHONE: 1-800-997-3876
FAX: 919-775-3541
www.zurn.com

Form No. FV365, 4/05

Aquaflush Z6000

ENGINEERING SPECIFICATION: ZURN Z6000 Aquaflush® Exposed Closet Flush Valve – Exposed, quiet diaphragm-type, chrome-plated, flushometer valve with a polished exterior. Complete with a chloramine resistant, dual seal diaphragm with a clog resistant by-pass. The valve is ADA compliant with a non-hold open and no leak handle feature, high back pressure vacuum breaker, one-piece hex coupling nut, adjustable tailpiece, spud coupling, and flange for top spud connection. Control stop has internal siphon-guard protection. Internal seals are made of chloramine resistant materials.

Flow Options

-WS1	1.6 Gallon Low Consumption Flush
-FF	4.5 Gallon Full Flush
Standard Flush	3.5 Gallons Per Flush

Suffix Options (Check/Specify Appropriate Options)

__	**-BG**	BioCare ADA Handle
__	**-H**	Handle on Front of Flush Valve
__	**-L**	1" [25] Metal Push Button
__	**-L3**	3" [76] Metal Push Button
__	**-VC**	Vandal-Resistant Stop Cover
__	**-YB**	Sweat Solder Kit
__	**-YC**	Cast Wall Flange
__	**-YJ**	Split Ring Pipe Support
__	**-YK**	Solid Ring Pipe Support
__	**-YO**	Bumper on Angle Stop
__		Other

Aquaflush Z6003

ENGINEERING SPECIFICATION: ZURN Z6003 Aquaflush® Exposed Urinal Flush Valve – Exposed, quiet diaphragm-type, chrome-plated, flushometer valve with a polished exterior. Complete with a chloramine resistant, dual seal diaphragm with a clog resistant by-pass. The valve is ADA compliant with a non-hold open and no leak handle feature, high back pressure vacuum breaker, one-piece hex coupling nut, adjustable tailpiece, spud coupling, and flange for top spud connection. Control stop has internal siphon-guard protection. Internal seals are made of chloramine resistant materials.

Flow Options

-EWS	0.5 Gallon Per Flush
-WS1	1.0 Gallon Low Consumption Flush
Standard Flush	1.5 Gallons Per Flush

Suffix Options (Check/Specify Appropriate Options)

__	**-BG**	BioCare ADA Handle
__	**-H**	Handle on Front of Flush Valve
__	**-L**	1" [25] Metal Push Button
__	**-L3**	3" [76] Metal Push Button
__	**-VC**	Vandal-Resistant Stop Cover
__	**-YB**	Sweat Solder Kit
__	**-YC**	Cast Wall Flange
__	**-YJ**	Split Ring Pipe Support
__	**-YK**	Solid Ring Pipe Support
__		Other