



# CLEAN POWER STEAM CLEANERS

The Clean Power Steam Cleaner is a revolutionary and environmentally friendly steam machine. Using the latest technology in steam generation, the Clean Power Steam Cleaner can quickly and effectively clean dirt, grease, other contaminants and remove odors from a variety of surfaces.



## benefits

- Clean, deodorize and sterilize general surfaces
- Quickly and easily remove dirt, stains and grease
- Virtually eliminate waste-water
- Virtually eliminate chemical consumption
- Clean difficult to reach nooks and crevices
- Easy to maintain and operate
- Simultaneous dual operation
- All day use
- Quiet operation

## cleaning application

- Clean cars, buses trucks, motorcycles, boats, golfcarts small planes, machinery and general surfaces
- Sanitation
- Food & beverage equipment
- Park and recreational equipment
- Property management services
- Military equipment
- Heavy industrial equipment
- Medical and hospital facilities

# features

## **Dual Spray guns**

Two operators can work together without loss in steam pressure and volume

## **Adjustable Moisture Control Valve**

Easily adjust from a dry steam to a wet steam

## **Hose Length**

Standard 33'(10m) of hose length, expandable up to 65'(20m) (Option)

## **Continuous Feed Water Connection**

Connect a water hose to receive continuous water supply to the unit steam

## **Heat Efficient and Self Regulating Stainless Steel Boiler**

Equipped with a diesel powered burner that produces initial steam within 2 minutes and automatically turns on and off to maintain operating pressure. The burner does not remain idle, reducing emissions, noise and fuel consumption. The boiler's unique stainless steel design supports a long life span and helps maintain the machine during extended periods of use.

## **Multiple Safety Features \***

Safety features include an LED illuminated control panel with corresponding alarm, automatic shut-offs, pressure sensor, automatic pressure release valve, thermostat control, fuel and water tank level sight glass and a dry-run prevention setting on the water pump.



# CP 9020A

## Diesel Powered

### Specifications:

Pressure	116 psi (max. 145 psi)
Operating Temperature	185°F~248°F
Preheating Time	10 minutes
Water Tank Capacity	5.28 gallons
Water Flow Rate (adjustable)	0.08 gpm x 2guns
Diesel Tank (10 HR continuous oper.)	4.75 gallons
Diesel Consumption Rate	.53 gph
Power Requirements	80 watts(4A), 110~120V, 50/60Hz
Weight	187 (lb)
Dimensions	27(L) x 26.8(W) x 29.5(H) in
Colors	Stainless steel
Steam Hose Length	33' (10m), 65' (20m) available (Option)
Spray Gun Nozzle Size	2.5mm
Anti-freeze protection	Yes
Warranty*	1 years from purchase date. (Accessories are not included)

### Standard

Pressure	116 psi (max. 145 psi)
Operating Temperature	185°F~248°F
Preheating Time	10 minutes
Water Tank Capacity	5.28 gallons
Water Flow Rate (adjustable)	0.08 gpm x 2guns
Diesel Tank (10 HR continuous oper.)	4.75 gallons
Diesel Consumption Rate	.53 gph
Power Requirements	80 watts(4A), 110~120V, 50/60Hz
Weight	187 (lb)
Dimensions	27(L) x 26.8(W) x 29.5(H) in
Colors	Stainless steel
Steam Hose Length	33' (10m), 65' (20m) available (Option)
Spray Gun Nozzle Size	2.5mm
Anti-freeze protection	Yes
Warranty*	1 years from purchase date. (Accessories are not included)

# CP 9020G

## Compact Gas Powered



### Specifications:

Pressure	116 psi
Operating Temperature	185°F~248°F
Preheating Time	15 Sec / 3pass, dual pipe heating technology
Water Tank Capacity	7.92 gallins
Water Flow Rate (adjustable)	0.08 gpm
Source Power	LPG gas
Operation control	on / off switch + Continuous operation (No pressure vessel)
Power requirements	80 watts (4A), 110V, 50/60 HZ (available in 220~240V, 50/60 HZ)
Weight	77 (lb)
Dimensions	24(L) x 18(W) x 22(H) in
Colors	Stainless steel
Steam Hose Length	33' (10m)
Spray Gun Nozzle Size	3.0mm
Anti-freeze protection	Yes
Warranty*	1 years from purchase date. (Accessories are not included)

### Standard

Pressure	116 psi
Operating Temperature	185°F~248°F
Preheating Time	15 Sec / 3pass, dual pipe heating technology
Water Tank Capacity	7.92 gallins
Water Flow Rate (adjustable)	0.08 gpm
Source Power	LPG gas
Operation control	on / off switch + Continuous operation (No pressure vessel)
Power requirements	80 watts (4A), 110V, 50/60 HZ (available in 220~240V, 50/60 HZ)
Weight	77 (lb)
Dimensions	24(L) x 18(W) x 22(H) in
Colors	Stainless steel
Steam Hose Length	33' (10m)
Spray Gun Nozzle Size	3.0mm
Anti-freeze protection	Yes
Warranty*	1 years from purchase date. (Accessories are not included)



# CP 9020S/SG

Diesel Powered/Gas Powered

## Specifications:

Pressure	116 psi (max. 145 psi)
Operating Temperature	194°F~203°F
Preheating Time	6 minutes
Water Tank Capacity	4.5 gallons
Water Flow Rate (adjustable)	0.08 gpm x 1 guns
Diesel Tank (10 HR continuous oper.)	2.32 gallons
Diesel Consumption Rate	.26 gph
Power Requirements	80 watts(4A), 110~120V, 50/60Hz
Weight	121 (lb)
Dimensions	25(L) x 20(W) x 26(H) in
Colors	Stainless steel
Steam Hose Length	33' (10m), 65' (20m) available (Option)
Spray Gun Nozzle Size	2.5mm
Anti-freeze protection	Yes
Warranty*	1 years from purchase date. (Accessories are not included)

## Standard

A side-view photograph of a silver van driving on a road. The van's side mirror and door are visible on the left. The road curves to the right, bordered by a field and trees. The sky is blue with large white clouds, which are reflected on the van's side panel. The text "THANK YOU" is overlaid in white, bold, sans-serif font in the center of the image.

**THANK YOU**

**ezsteam.net**

For additional questions or comments,  
feel free to contact us at [info@ezsteam.net](mailto:info@ezsteam.net)